

YEONG TZAW ASSOCIATES INC

YT-1900A-SS

COMPUTER CONTROLLED DIRECT DRIVE BAR TAKING MACHINE

YT-1903A

COMPUTER CONTROLLED DIRECT DRIVE BUTTOM SEAM MACHINE



Features:

- The patented Automatic detected function for the fabric thickness. The machine will follow the feedback of needle tip detective to increase or decrease the stitch power, Don't need to set it up
- The real operation speed for YT-1900A-SS is 3,000 rpm/minute. The real operation speed for YT-1903A is 2,700 rpm/minute.
- Micro-Lubrication system: The needle bar, thread take-up, front cover don't requires any lubrication. To solve the leaking problem
- The simplify Control panel leave the Selection key out. To pick up the adjusted items directly, simply and fast to find the needed functions. Memorized sewing machine. The machine Could offer max. 25 difference stitches in a cycle seam It's could record 200 difference stitches.
- The stitch could follow user's demand to design by themselves except the regular stitches.
- Buy an extra accessory and chip to make the machine with bar taking(YT-1900) and bottom seam(YT-1903A) function.

Model	YT-1903A
Speed	Max:3000rpm
Needle System	DPX5


9F NO. 659 ZHONG ZHENG RD.,
XINZHUANG DISTRICT
24257 NEW TAIPEI CITY TAIWAN.
www.sewingpart.com.tw

TEL:886-2-29060325
FAX:886-2-29035545
E-MAIL:info@ytai.com.tw

YEONG TZAW ASSOCIATES INC

No	落針圖	針數	縫製尺寸 (mm)		(注2) 壓腳號碼					
			縱	橫						
大 固 定	1 (51)		2.0	16	1					
				2						
	2		2.0	10	1					
				2						
	3		2.5	16	1					
				4						
	4		3.0	24	6					
				7						
	5		2.0	10	1					
				2						
6		2.5	16	1						
			4							
7		2.0	10	1						
			2							
8		2.5	16	1						
			4							
9		56	3.0	24	6					
			7							
10		64	3.0	24	6					
			7							
小 固 定		21	2.5	6	8					
						12	28	2.5	6	8
針 織 固 定		14	2.0	8	5					
						15	21	2.0	8	5

No	落針圖	針數	縫製尺寸 (mm)		(注2) 壓腳號碼	
			縱	橫		
線 固 定	17	21	0	10	1	
				2		
	18		0	10	1	
				2		
	19		0	25	6	
				7		
	20		36	0	25	6
				7		
	21		41	0	25	6
				7		
22		44	0	35	(注3)	
縱 固 定	23	28	20	4.0	9	
				4.0		
	24	36	20	4.0		4.0
				4.0		
	25	42	20	4.0		4.0
				4.0		
26	56	20	4.0	4.0		
			4.0			
縱 線 固 定	27	18	20	0	11	
				0		
	28	21	10	0		0
				0		
	29	20	0	0		0
0						
30	28	20	0	0		
			0			


 1. 縫製尺寸為放大率100%的尺寸。
 2. 壓腳號碼請參照壓腳一覽表。
 3. No. 22為加工半成品時使用。
 4. ※標記圖案為縫製牛仔布料用。
 5. No. 51為無批發用。

No.	落針圖	針數	縫製尺寸 (mm)		
			縱	橫	
半 月 形 加 固	31	52	7	10	
			12		
	32		63	7	12
				10	
	33		24	6	10
				12	
34		31	6	12	
			7		
35		48	10	7	
			7		
36		48	10	7	
			7		
大 固 定		90	3	24	
			8		
針 織 固 定		28	2	8	
			8		
圓 形 加 固		28	Ø12		
			48		

(注意)
 圖案No. 41~46是請參閱No. 12用。
 線加與縫業No. 23~26在原點5mm上下不同。

No.	落針圖	針數	縫製尺寸 (mm)						
			縱	橫					
縱 固 定	41	29	20	2.5					
			2.5						
	42		39	25	2.5				
				2.5					
	43		45	25	2.5				
2.5									
44		58	30	2.5					
			2.5						
45		75	30	2.5					
			2.5						
46		42	30	25					
			25						
菊 花 鎖 眼		91	Ø8						
			99	148	164				
						148	164		
								148	164